



# PATTERSON RENTAL TOOLS

## 1 1/4" 3.02# T-95 CS Hydril Type Tubing

<b>Product:</b>	<b>1 1/4"</b>	TUB114CST95
<b>Tube Size:</b>	1.660"	In.
<b>Nominal Weight / Ft.:</b>	3.02	Lbs./Ft.
<b>Tube Grade:</b>	T-95	
<b>Connection:</b>	1 1/4" CS HYD.	
<b>Hard Banding/Coating:</b>	NONE	
<b>Tube Specifications</b>		
<b>Inside Diameter:</b>	1.278"	In.
<b>Wall Thickness:</b>	.191"	In.
<b>Tensile Yield New:</b>	84,000	Lbs.
<b>Premium:</b>	67,200	Lbs.
<b>PSI Burst (New / Test):</b>	19130 / 17500	PSI
<b>Collapse (100% / 80%):</b>	19350 / 15480	PSI
<b>Engineering Data:</b>		
<b>Drift Diameter:</b>	1.184"	In.
<b>Average Joint Length :</b>	31	Feet
<b>Displacement(Open):</b>	0.046	Gal./Ft.
	0.110	Bbl./100 Ft.
<b>Capacity:</b>	0.066	Gal./Ft.
	0.157	Bbl./100 Ft.
<b>Connection Specifications</b>		
<b>Outside Diameter:</b>	1.927"	In.
<b>Inside Diameter:</b>	1.218"	In.
<b>Make Up Min:</b>	600	Ft-Lbs
<b>Make Up Max:</b>	750	Ft-Lbs
<b>ID. Markings:</b>	1 GROOVE (1/4")	
<b>Stencil Markings:</b>	"PT"	
<b>Torsional Yield:</b>	1,719	Ft-Lbs

\* Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Patterson Services, Inc. makes no representation about, and is not responsible or liable for the accuracy or reliability of the data, described herein. Nothing contained in this document shall be considered a recommendation for any use that may infringe patent rights, or an endorsement of any particular material, equipment, service, or other item. The properties listed in this document are not specification. They are provided as information only and in no way modify, amend, enlarge or create any specification or warranty.



### Tubing

1" thru 4 1/2"

### Drill Pipe

2 3/8" thru 5 1/2"

### Heavy Weight Drill Pipe

2 7/8" thru 6 5/8"

### Drill Collars

2 7/8" thru 10"

### Blow-Out Preventers

#### Annular Type

2 9/16" 5M thru 29 1/2" 500 PSI

#### Hydraulic Ram Type

#### Single and Double

3 1/16" 10M thru 16 3/4" 5M

### Valves Manual & Hydraulic

#### 12" Ball Valves

2 1/16" 5M thru 4 1/16" 15M