



PATTERSON RENTAL TOOLS

2 7/8" BN 10.40# S-135 AOH Drill Pipe

Product:	2 7/8" BN	DP278BNS135W278AOH
Tube Size:	2 7/8"	In.
Nominal Weight / Ft.:	10.40#	Lbs./Ft.
Tube Grade:	S-135	
Connection:	2 7/8" AOH	
Tube Specifications		
Inside Diameter:	2.151	In.
Wall Thickness:	0.362	In.
Tensile Yield New:	385,830	Lbs.
Premium:	308,664	Lbs.
Torsional Yield New:	20,800	Ft-Lbs.
Premium:	15,900	Ft-Lbs.
PSI Burst (New/Premium):	29747 / 28640	PSI
Collapse (New/Premium):	29716 / 25602	PSI
Engineering Data:		
Drift Diameter:	1.963	In.
Adj. Weight / Foot:	11.01	Lbs./Ft.
Avg Jt Length / Jt Weight:	31'	Feet Lbs.
Displacement(Open):	0.168	Gal./Ft.
	0.400	Bbl./100 Ft.
Capacity:	0.189	Gal./Ft.
	0.450	Bbl./100 Ft.
Connection Specifications		
Outside Diameter:	3 7/8"	In.
Minimum OD	3 5/8"	In.
Inside Diameter:	2 5/32"	In.
Tensile Yield New:	345,500	Lbs.
Premium:	276,400	Lbs.
Torsional Strength New:	8,800	Ft./lbs.
Maximum Torque New:	4,800	Ft./lbs.
Minimum Torque New:	4,400	Ft./lbs.
Make Up Torque:		
ID. Markings:	1 groove	
Minimum usage lengths:	Box 4 1/2" Pin 4"	
Special Note:		

* Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Patterson Services, Inc. makes no representation about, and is not responsible or liable for the accuracy or reliability of the data, described herein. Nothing contained in this document shall be considered a recommendation for any use that may infringe patent rights, or an endorsement of any particular material, equipment, service, or other item. The properties listed in this document are not specification. They are provided as information only and in no way modify, amend, enlarge or create any specification or warranty.



Tubing

1" thru 4 1/2"

Drill Pipe

2 3/8" thru 5 1/2"

Heavy Weight Drill Pipe

2 7/8" thru 6 5/8"

Drill Collars

2 7/8" thru 10"

Blow-Out Preventers

Annular Type

2 9/16" 5M thru 29 1/2" 500 PSI

Hydraulic Ram Type

Single and Double

3 1/16" 10M thru 16 3/4" 5M

Valves Manual & Hydraulic

12" Ball Valves

2 1/16" 5M thru 4 1/16" 15M