



PATTERSON RENTAL TOOLS

3 1/8" Spiral/Plain W/2 3/8" Reg.

Tubing

1" thru 4 1/2"

Drill Pipe

2 3/8" thru 5 1/2"

Heavy Weight Drill Pipe

2 7/8" thru 6 5/8"

Drill Collars

2 7/8" thru 10"

Blow-Out Preventers

Annular Type

2 9/16" 5M thru 29 1/2" 500 PSI

Hydraulic Ram Type

Single and Double

3 1/16" 10M thru 16 3/4" 5M

Valves Manual & Hydraulic

12" Ball Valves

2 1/16" 5M thru 4 1/16" 15M

Product:	3 1/8" Spiral/Plain Drill Collar	DC318P238REG
Tube Size:	3.125	In.
Plain Nominal Weight/Jt	681/660	Lbs
Spiral Nominal Weight/JT	660	Lbs
Connection:	2 3/8" Regular	
Engineering Data:		
Avg Jt Length	30	Feet
Displacement(Open):	0.335	Gal./Ft.
	0.798	Bbl./100 Ft.
Capacity:	0.064	Gal./Ft.
	0.152	Bbl./100 Ft.
Connection Specifications		
Outside Diameter:	3.125	In.
Minimum OD	3.00	In.
Inside Diameter:	1.125/1.250	In.
Tensile Yield New:	295,800	Lbs.
Torsional Strength New:	5,300	Ft-Lbs
Make Up Torque Min New:	3,000	Ft./lbs.
Make Up Torque Max New:	3,300	Ft./lbs.
Special Note:		
Minimum length Box & Pin	6"	

* Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Patterson Services, Inc. makes no representation about, and is not responsible or liable for the accuracy or reliability of the data, described herein. Nothing contained in this document shall be considered a recommendation for any use that may infringe patent rights, or an endorsement of any particular material, equipment, service, or other item. The properties listed in this document are not specification. They are provided as information only and in no way modify, amend, enlarge or create any specification or warranty.

