



PATTERSON RENTAL TOOLS

3 1/2" BN SHWDP W/3 1/2" IF

Product:	3 1/2" BN SHWDP	HWS312
Tube Size:	3 1/2"	In.
Nominal Weight/JT	828	Lbs
Connection:	3 1/2" IF	
Engineering Data:		
Drift Diameter:	2	In.
Adj. Weight / Foot:	26.70#	Lbs./Ft.
Avg Jt Length	30'	Feet
Displacement(Open):	0.388	Gal./Ft.
	0.924	Bbl./100 Ft.
Capacity:	0.206	Gal./Ft.
	0.490	Bbl./100 Ft.
Connection Specifications		
Outside Diameter:	4 7/8"	In.
Minimum OD	4 19/32"	In.
Inside Diameter:	2 1/4"	In.
Tensile Yield New:	310,500	Lbs.
Torsional Strength New:	22,900	Ft/lbs.
Make Up Torque Min New:	11,500	Ft/lbs.
Make Up Torque Max New:	13,700	Ft/lbs.
Special Note:		
Minimum length Box:	6 "	
Minimum length Pin:	6 "	

Tubing

1" thru 4 1/2"

Drill Pipe

2 3/8" thru 5 1/2"

Heavy Weight Drill Pipe

2 7/8" thru 6 5/8"

Drill Collars

2 7/8" thru 10"

Blow-Out Preventers

Annular Type

2 9/16" 5M thru 29 1/2" 500 PSI

Hydraulic Ram Type

Single and Double

3 1/16" 10M thru 16 3/4" 5M

Valves Manual & Hydraulic

12" Ball Valves

2 1/16" 5M thru 4 1/16" 15M

* Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Patterson Services, Inc. makes no representation about, and is not responsible or liable for the accuracy or reliability of the data, described herein. Nothing contained in this document shall be considered a recommendation for any use that may infringe patent rights, or an endorsement of any particular material, equipment, service, or other item. The properties listed in this document are not specification. They are provided as information only and in no way modify, amend, enlarge or create any specification or warranty.

