



PATTERSON RENTAL TOOLS

4.0" 14.00 # S-135 DS-38 Drill Pipe

Product:	4" SLIM HOLE	DP4SHS135WDS38
Tube Size:	4"	In.
Nominal Weight / Ft.:	14#	Lbs./Ft.
Tube Grade:	S-135	
Connection:	DS-38	
Tube Specifications		
Inside Diameter:	3.340	In.
Wall Thickness:	0.330	In.
Tensile Yield New:	513,600	Lbs.
Premium:	410,920	Lbs.
Torsional Yield New:	41900	Ft-Lbs.
Premium:	32800	Ft-Lbs.
PSI Burst (New/Premium):	19491 / 17820	PSI
Collapse (New/Premium):	20141 / 13836	PSI
Engineering Data:		
Drift Diameter:	2.313 (IPC 2.293)	In.
Adj. Weight / Foot:	15.64	Lbs./Ft.
Avg Jt Length / Jt Weight:	31'	Feet Lbs.
Displacement(Open):	0.239	Gal./Ft.
	0.569	Bbl./100 Ft.
Capacity:	0.434	Gal./Ft.
	1.038	Bbl./100 Ft.
Connection Specifications		
Outside Diameter:	4 7/8"	In.
Minimum OD	4 19/32"	In.
Inside Diameter:	2 7/16	In.
Tensile Yield New:	708,100	Lbs.
Premium:	665,614	Lbs.
Torsional Strength New:	28,600	Ft./lbs
Maximum Torque New:	17,100	Ft./lbs.
Minimum Torque New:	12,900	Ft./lbs.
Make Up Torque:		
ID. Markings:	1 groove	
Minimum usage lengths:	Box 6 1/2" Pin 6"	
Special note:	Compatible with IF (NC-38)	

* Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Patterson Services, Inc. makes no representation about, and is not responsible or liable for the accuracy or reliability of the data, described herein. Nothing contained in this document shall be considered a recommendation for any use that may infringe patent rights, or an endorsement of any particular material, equipment, service, or other item. The properties listed in this document are not specification. They are provided as information only and in no way modify, amend, enlarge or create any specification or warranty.



Tubing

1" thru 4 1/2"

Drill Pipe

2 3/8" thru 5 1/2"

Heavy Weight Drill Pipe

2 7/8" thru 6 5/8"

Drill Collars

2 7/8" thru 10"

Blow-Out Preventers

Annular Type

2 9/16" 5M thru 29 1/2" 500 PSI

Hydraulic Ram Type

Single and Double

3 1/16" 10M thru 16 3/4" 5M

Valves Manual & Hydraulic

12" Ball Valves

2 1/16" 5M thru 4 1/16" 15M