



PATTERSON RENTAL TOOLS

4 1/2" BN 16.60# S-135T XTM-43 Drill Pipe

Product:	4 1/2" BN	DP412BNS1351660XTM43
Tube Size:	4 1/2"	In.
Nominal Weight / Ft.:	16.60#	Lbs./Ft.
Tube Grade:	S-135T	
Connection:	XTM-43	
Tube Specifications		
Inside Diameter:	3.826	In.
Wall Thickness:	0.337	In.
Tensile Yield New:	595,000	Lbs.
Premium:	476,000	Lbs.
Torsional Yield New:	55,500	Ft-Lbs.
Premium:	43,500	Ft-Lbs.
PSI Burst (New/Premium):	17693 / 16176	PSI
Collapse (New/Premium):	16733 / 10964	PSI
Engineering Data:		
Drift Diameter:	2.875 (IPC 2.855)	In.
Adj. Weight / Foot:	17.92	Lbs./Ft.
Avg Jt Length / Jt Weight:	31'	Feet Lbs.
Displacement(Open):	0.274	Gal./Ft.
	0.652	Bbl./100 Ft.
Capacity:	0.581	Gal./Ft.
	1.383	Bbl./100 Ft.
Connection Specifications		
Outside Diameter:	5 1/4"	In.
Minimum OD	5 5/32"	In.
Inside Diameter:	3"	In.
Tensile Yield New:	764,500	Lbs.
Premium:	718,630	Lbs.
Torsional Strength New:	39,200	
Maximum Torque New:	23,500	
Minimum Torque New:	19,600	
Make Up Torque:		
ID. Markings:	none	
Minimum usage lengths:	Box 8" Pin 6"	
Special Note:		

* Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Patterson Services, Inc. makes no representation about, and is not responsible or liable for the accuracy or reliability of the data, described herein. Nothing contained in this document shall be considered a recommendation for any use that may infringe patent rights, or an endorsement of any particular material, equipment, service, or other item. The properties listed in this document are not specification. They are provided as information only and in no way modify, amend, enlarge or create any specification or warranty.



Tubing

1" thru 4 1/2"

Drill Pipe

2 3/8" thru 5 1/2"

Heavy Weight Drill Pipe

2 7/8" thru 6 5/8"

Drill Collars

2 7/8" thru 10"

Blow-Out Preventers

Annular Type

2 9/16" 5M thru 29 1/2" 500 PSI

Hydraulic Ram Type

Single and Double

3 1/16" 10M thru 16 3/4" 5M

Valves Manual & Hydraulic

12" Ball Valves

2 1/16" 5M thru 4 1/16" 15M