



# PATTERSON RENTAL TOOLS

## 5 1/2" BN 24.70# S-135 XT-57 Drill Pipe

<b>Product:</b>	<b>5 1/2" BN</b>	<b>DP512BNS135XT57</b>
<b>Tube Size:</b>	<b>5 1/2"</b>	<b>In.</b>
<b>Nominal Weight / Ft.:</b>	<b>24.7#</b>	<b>Lbs./Ft.</b>
<b>Tube Grade:</b>	<b>S-135</b>	
<b>Connection:</b>	<b>XT-57</b>	
<b>Tube Specifications</b>		
<b>Inside Diameter:</b>	<b>4.670</b>	<b>In.</b>
<b>Wall Thickness:</b>	<b>0.415</b>	<b>In.</b>
<b>Tensile Yield New:</b>	<b>895,000</b>	<b>Lbs.</b>
<b>Premium:</b>	<b>704,300</b>	<b>Lbs.</b>
<b>Torsional Yield New:</b>	<b>101,800</b>	<b>Ft-Lbs.</b>
<b>Premium:</b>	<b>79,800</b>	<b>Ft-Lbs.</b>
<b>PSI Burst (New/Premium):</b>	<b>17826 / 16298</b>	<b>PSI</b>
<b>Collapse (New/Premium):</b>	<b>17023 / 11177</b>	<b>PSI</b>
	<b>4.670</b>	
<b>Drift Diameter:</b>	<b>4.125 (IPC 4.105)</b>	<b>In.</b>
<b>Adj. Weight / Foot:</b>	<b>27.82</b>	<b>Lbs./Ft.</b>
<b>Avg Jt Length / Jt Weight:</b>	<b>31'</b>	<b>Feet Lbs.</b>
<b>Displacement(Open):</b>	<b>0.426</b>	<b>Gal./Ft.</b>
	<b>1.014</b>	<b>Bbl./100 Ft.</b>
<b>Capacity:</b>	<b>0.879</b>	<b>Gal./Ft.</b>
	<b>2.093</b>	<b>Bbl./100 Ft.</b>
<b>Connection Specifications</b>		
<b>Outside Diameter:</b>	<b>7"</b>	<b>In.</b>
<b>Minimum OD</b>	<b>6 7/16"</b>	<b>In.</b>
<b>Inside Diameter:</b>	<b>4 1/4"</b>	<b>In.</b>
<b>Tensile Yield New:</b>	<b>1,208,700</b>	<b>Lbs.</b>
<b>Premium:</b>	<b>1,136,178</b>	<b>Lbs.</b>
<b>Torsional Strength New:</b>	<b>94,300</b>	<b>Ft./lbs.</b>
<b>Maximum Torque New:</b>	<b>56,600</b>	<b>Ft./lbs.</b>
<b>Minimum Torque New:</b>	<b>33,800</b>	<b>Ft./lbs.</b>
<b>Make Up Torque:</b>		
<b>ID. Markings:</b>	<b>1 groove</b>	
<b>Minimum usage lengths:</b>	<b>Box 8.26" Pin 6"</b>	
<b>Special Note:</b>		

\* Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Patterson Services, Inc. makes no representation about, and is not responsible or liable for the accuracy or reliability of the data, described herein. Nothing contained in this document shall be considered a recommendation for any use that may infringe patent rights, or an endorsement of any particular material, equipment, service, or other item. The properties listed in this document are not specification. They are provided as information only and in no way modify, amend, enlarge or create any specification or warranty.



### Tubing

1" thru 4 1/2"

### Drill Pipe

2 3/8" thru 5 1/2"

### Heavy Weight Drill Pipe

2 7/8" thru 6 5/8"

### Drill Collars

2 7/8" thru 10"

### Blow-Out Preventers

#### Annular Type

2 9/16" 5M thru 29 1/2" 500 PSI

#### Hydraulic Ram Type

#### Single and Double

3 1/16" 10M thru 16 3/4" 5M

### Valves Manual & Hydraulic

#### 12" Ball Valves

2 1/16" 5M thru 4 1/16" 15M