



# PATTERSON RENTAL TOOLS

## 8" Spiral/Plain Drill Collar W/NC-56

<b>Product:</b>	<b>8" Spiral/Plain Drill Collar</b>	DC8SNC56
<b>Tube Size:</b>	8"	In.
<b>Plain Nominal Weight/Jt</b>		Lbs
<b>Spiral Nominal Weight/JT</b>	4,343	Lbs
<b>Connection:</b>	NC-56	
<b>Engineering Data:</b>		
<b>Avg Jt Length</b>	30	Feet
<b>Displacement(Open):</b>	2.288	Gal./Ft.
	5.448	Bbl./100 Ft.
<b>Capacity:</b>	0.323	Gal./Ft.
	0.769	Bbl./100 Ft.
<b>Connection Specifications</b>		
<b>Outside Diameter:</b>	8"	In.
<b>Minimum OD</b>	7 3/4"	In.
<b>Inside Diameter:</b>	2 13/16"	In.
<b>Tensile Yield New:</b>	1,734,400	Lbs.
<b>Torsional Strength New:</b>	77,200	Ft./lbs.
<b>Make Up Torque Min New:</b>	48,300	Ft./lbs.
<b>Make Up Torque Max New:</b>	53,000	Ft./lbs.
<b>Special Note:</b>		
<b>Minimum length Box &amp; Pin</b>	7"	

\* Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Patterson Services, Inc. makes no representation about, and is not responsible or liable for the accuracy or reliability of the data, described herein. Nothing contained in this document shall be considered a recommendation for any use that may infringe patent rights, or an endorsement of any particular material, equipment, service, or other item. The properties listed in this document are not specification. They are provided as information only and in no way modify, amend, enlarge or create any specification or warranty.



### Tubing

1" thru 4 1/2"

### Drill Pipe

2 3/8" thru 5 1/2"

### Heavy Weight Drill Pipe

2 7/8" thru 6 5/8"

### Drill Collars

2 7/8" thru 10"

### Blow-Out Preventers

#### Annular Type

2 9/16" 5M thru 29 1/2" 500 PSI

#### Hydraulic Ram Type

##### Single and Double

3 1/16" 10M thru 16 3/4" 5M

### Valves Manual & Hydraulic

#### 12" Ball Valves

2 1/16" 5M thru 4 1/16" 15M