

# HWDP Data & Performance Sheet

## 4" Plain Hevi-Wate DP DS-38

### TUBE BODY DATA

Tube OD	4.000	in.
Wall Thickness	0.719	in.
Tube ID	2.563	in.
Pipe Grade	55,000	psi.
Tensile Yield Strength	407,500	lbs.
Torsional Yield Strength	27,600	ft-lbs.
Tube Burst	17,300	psi.
Tube Collapse	16,200	psi.
Elevator Capacity	337,000	lbs.
Slip-Crush Capacity (16.5" gripper contact length)	306,400	lbs.

### CONNECTION DATA

Connection	DS-38	
Tool Joint OD	5.000	in.
Tool Joint ID	2.563	in.
Tool Joint SMYS	120,000	psi.

### CONNECTION PERFORMANCE

Make Up Torque (Max.) <sup>1</sup>	15,400	ft-lbs. (1.0 FF)
	17,710	ft-lbs. (1.15 FF)
Connection Tensile Yield (@ Max. M/U TQ)	555,800	lbs.
Connection Torsional Yield	25,600	ft-lbs.

### ENGINEERING DATA

Approximate Length	30	ft.		
Drift Diameter	2.438	in.		
Adj. Weight	29.92	lbs. / ft.		
Displacement	0.4676	gal. / ft.	0.0111	bbls. / ft.
Capacity	0.2631	gal. / ft.	0.0063	bbls. / ft.

### Notes:

- <sup>1</sup>Max MUT 1.0 FF is 60% of connection torsional strength. Stick and slip is very damaging to connections and can induce higher-than-planned torque. As required, adjust MUT according to applied thread compound friction factor, not exceeding 1.15. Higher MUT should only be applied where rotary torque exceeds 80% 1.0 FF or when downhole torque and/or backoff is a concern.
- Dimensions, wall thickness, and lengths shown above are nominal. Figures may exclude the effects of wear, stress relief, boreback, ID chamfers, and/or spiral features.

The technical information contained herein, including the product performance sheet and other attached documents, has been extracted from information available from the manufacturer and is for reference only and not a recommendation. The user is fully responsible for the accuracy and suitability of use of the technical information. Patterson Services, Inc. cannot assume responsibility for the results obtained through the use of this material. No expressed or implied warranty is intended. Heavy-weight drill pipe assembly properties are calculated based on uniform OD and wall thickness. No safety factor is applied. Weight, displacement, and capacity are approximate and can vary by ± 10% (or more) depending on OD, specified wall, wall tolerance, and internal coating options. It is the responsibility of the customer and the end user to determine the appropriate performance ratings, acceptable use of the product, maintain safe operational practices, and to apply a prudent safety factor suitable for the application. For API connections that have different pin and box IDs, tool joint ID refers to the pin ID. Per Chapter B, Section 4 VII of the IADC drilling manual, it is recommended that drilling torque should not exceed 80% of MUT.